

# FRAMES AUSRACK PLUS FRAME

## Overview

Ausrack Plus frames are flexible open frame solutions, with optional accessories, such as side panels and doors, which can be added to the frame where required. Designed with a high load rating and inset posts it combines versatility and strength with easy to use features.



## Features

- EIA-310-D and SSI standards compliant
- Robust fully-welded frame design
- Load Ratings – Static (UDL) 1400kg; Seismic 900kg
- Frame design enables two or more people to work on installation at once
- Setback post position allows for easier cabling to equipment and patching from cable zones
- Cable entry points in top and bottom plinth
- Depth adjustable RU marked mounting rails
- Optional partial height rails for variable mounting of equipment
- Optional modular cable zone
- Optional baying kit
- Textured matt black powdercoat finish
- Comprehensive range of accessories

## Inclusions

- 4 post 19" frame suitable for network & server applications
- RU labelled mounting rails (x4)
- Flat top cover (24RU racks only)
- Gland plates fitted to roof (40 & 45RU racks only)
- Bolt down brackets

## Model Sizes

### 600mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AF24U606	24	1202	600	600
AF24U609	24	1202	600	900
AF24U611	24	1202	600	1100
AF40U606	40	1913	600	600
AF40U609	40	1913	600	900
AF40U611	40	1913	600	1100
AF45U606	45	2135	600	600
AF45U609	45	2135	600	900
AF45U611	45	2135	600	1100

For dimension drawing see page 56

### 800mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AF40U809	40	1913	800	900
AF40U811	40	1913	800	1100
AF45U809	45	2135	800	900
AF45U811	45	2135	800	1100

For dimension drawing see page 57

## Accessories Guide

Accessories	Page
Doors and side panels	12 – 13
Cable zone	14
Cable management	15
Power rails	16
Shelves	17
Cable trays	18
Blanking panels	18
Fan kit	19
General accessories	19