

Overview

Ausrack Lite is a cost effective, well specified 19" network rack for small business or standalone applications. It offers a contemporary look with a safety glass front door, metal rear door and removable side panels in a neutral powdercoat finish.



Features

- EIA-310-D and SSI Standards compliant
- Static load rating of 500kg
- Three cable entry points in the base and one in the top
- Depth adjustable RU marked and notched rails
- Frame thickness 1.2mm
- Rail thickness 2.0mm
- Safety glass front window
- Powdercoat neutral grey
- Range of inclusive accessories

Inclusions

- Frame
- Four full height RU rails
- Front safety glass door
- Rear steel door
- Side panels (x2)
- Separate keys for front and rear door locks
- Fixed shelf/s
- Six way power rail
- Roof mounted fan tray kit
- Adjustable feet and castors
- Gland Plate
- Earthing point

Model Sizes

Complete Cabinets

Ausrack Lite complete cabinets consist of a frame, front and rear pair of RU marked and notched rails, front safety glass window door and rear steel door, two side panels and accessories.

Model No	Height (RU)	Dimensions (mm)		
		Height*	Width	Depth
ARLB6622U	22	1115	600	600
ARLB6822U	22	1115	600	800
ARLB6642U	42	1995	600	600
ARLB6842U	42	1995	600	800
ARLB6942U	42	1995	600	960
ARLB6647U	47	2220	600	600
ARLB6847U	47	2220	600	800
ARLB6947U	47	2220	600	960

*Height does not include feet or castors

For dimension drawing see page 63

Accessories Included

Model No	Safety glass front door	Steel rear door	Side Panels	Fixed Shelves	Power Rail 6-way	Fan Kit	Castors (set of 4)	Feet (set of 4)
ARLB6622U	1	1	2	1	1	2 unit	1	1
ARLB6822U	1	1	2	1	1	4 unit	1	1
ARLB6642U	1	1	2	3	1	2 unit	1	1
ARLB6842U	1	1	2	3	1	4 unit	1	1
ARLB6942U	1	1	2	3	1	4 unit	1	1
ARLB6647U	1	1	2	3	1	2 unit	1	1
ARLB6847U	1	1	2	3	1	4 unit	1	1
ARLB6947U	1	1	2	3	1	4 unit	1	1