



AUSRACK WALL

Ausrack Wall mount enclosures are robust, cost effective, easy to install 19" cabinets. They are used for smaller applications such as housing patch panels and network apparatus, where floor space is at a premium.

Available in two configurations, the Ausrack Wall is flexible in its application. For a cost effective cabinet the basic frame can be used to install equipment quickly and easily.

If accessibility is a priority, the swing frame option is perfect for applications that require easy installation or restricted maintenance. The rear swing frame can be fixed to the wall before attaching the body of the enclosure with no need for any additional drilling. As the rear frame has a separate key, access to the back of equipment is restricted to network administrators, whilst still allowing staff to access the controls on the front.

The cabinets are manufactured from robust Zincaneal<sup>®</sup> steel, with a highly durable neutral colour ripple powdercoat finish. The neutral colour helps to ensure that once installed, the rack does not look too large and dominant in a room.

Assembly time of equipment into the cabinet has also been reduced with an extra wide body designed to assist cable management and by the use of innovative rack rails that interlock with the bottom shelf. This allows the rails to be moved simply and easily then locked into the required position in the minimum of time.



## TECHNICAL INFORMATION

The Ausrack® Wall includes provision for cable ties on the front and rear of the cabinet, as well as a load bearing bottom shelf as a standard feature. The rear door option also allows for surface mounting cable entry, with handy cutouts in the door frame.

Model	RU	Height	Width	Depth
AR6U350	6	340	650	340
AR12U350	12	607	650	340
AR18U350	18	874	650	340
AR6U450	6	340	650	490
AR12U450	12	607	650	490
AR18U450	18	874	650	490
AR6U350NF	6	340	650	279
AR12U350NF	12	607	650	279
AR18U350NF	18	874	650	279
AR6U450NF	6	340	650	429
AR12U450NF	12	607	650	429
AR18U450NF	18	874	650	429

## SPECIAL FEATURES

The Ausrack® Wall is a result of extensive market research and testing. The special features we have incorporated as part of the range include:

- Robust construction
- High quality finish
- Reversible doors
- Load bearing bottom shelf
- 40kg load bearing capacity
- Extra wide body for superior cable management
- Lift off hinges on rear door

Please request our Data & Communications Catalogue or visit our website for more information on the Ausrack® Wall and other B&R Data Systems products.

## ACCESSORIES

RU	Depth	Fixed Shelf	Cantilever Shelf	Power Rail Bracket	Power Rail	Fan Kit
6	340	-	○	○	○	○
12		-	○	○	○	○
18		-	○	○	○	○
6	490	○	○	○	○	○
12		○	○	○	○	○
18		○	○	○	○	○

### SALES OFFICES

QLD (Brisbane) Ph 07 3714 1100

NSW (Sydney) Ph 02 9687 0077

VIC (Melbourne) Ph 03 8588 8400

SA (Adelaide) Ph 08 8243 1166

WA (Perth) Ph 08 9248 9744

[www.brdatasystems.com.au](http://www.brdatasystems.com.au)