

Overview

Ausrack Plus Network accommodates medium to large passive patching networks and active communications equipment. With the addition of Cable Zones, tailored functional cable management solutions can be incorporated to suit any network application.



Features

- EIA-310-D and SSI standards compliant
- Robust fully-welded frame design
- Load Ratings – Static (UDL) 1400kg; Seismic 900kg
- Frame design enables two or more people to work on installation at once
- Setback post position allows for easier cabling to equipment and patching from cable zones
- Cable entry points in top and bottom plinth
- Depth adjustable RU marked mounting rails
- Front acrylic window door and rear steel door
- 2 point door locking on all doors
- Optional 3 point door locking
- Key lockable wing knob
- Hinging allows standard door to open to the left or right side (customer changeable)
- Side panels with venting
- Optional modular cable zone
- Optional baying kit
- Optional side panel lock kit
- Textured matt black powdercoat finish
- Comprehensive range of accessories

Inclusions

- Rack frame
- RU labelled mounting rails (x4)
- Front acrylic window door and rear steel door
- 2-point locking doors with key lockable wing knob
- Side panels (x2)
- Flat top cover (24RU racks only)
- Gland plates fitted to roof (40 & 45RU racks only)
- Bolt down brackets

Model Sizes

600mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AN24U606	24	1202	600	600
AN24U609	24	1202	600	900
AN40U606	40	1913	600	600
AN40U609	40	1913	600	900
AN45U606	45	2135	600	600
AN45U609	45	2135	600	900

For dimension drawing see page 56

800mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AN40U809	40	1913	800	900
AN45U809	45	2135	800	900

For dimension drawing see page 57



Accessories Guide

Accessories	Page
Cable zone	14
Cable management	15
Power rails	16
Shelves	17
Cable trays	18
Blanking panels	18
Fan kit	19
General accessories	19