

Overview

Ausrack Plus Server is the essential platform for flexible computing solutions. It is a robust, 19" rack infrastructure solution designed for server applications in a data room environment. With an enhanced design as part of an infrastructure approach to issues of power, cooling and cable management, the Ausrack Plus Server offers a total solution for server applications.

With a range of sizes, configurations, features and functionality, the Ausrack Plus Server is an ideal choice for your IT server rack infrastructure.



Features

- EIA-310-D and SSI standards compliant
- Robust fully-welded frame design
- Load ratings – Static (UDL) 1400 kg; Seismic 900 kg
- Frame design enables two or more people to work on installation at once
- Setback post position allows for easier cabling to equipment and patching from cable zones
- Cable entry points in top and bottom plinth
- Depth adjustable RU marked mounting rails
- 63% open mesh doors on 600mm wide cabinets
- Split mesh doors on 800mm wide cabinets
- 2 point door locking on all doors
- Optional 3 point door locking
- Key lockable wing knob
- Hinging allows standard door to open to the left or right side (customer changeable)
- Side panels with venting
- Optional modular cable zone
- Optional server stabiliser kit
- Optional baying kit
- Optional side panel lock kit
- Textured matt black powdercoat finish
- Comprehensive range of accessories

Inclusions

- Rack frame
- RU labelled mounting rails (x4)
- Front and rear 63% open mesh doors on 600mm wide cabinets
- Front and rear split mesh doors on 800mm wide cabinets
- 2-point locking doors with key lockable wing knob
- Side panels (x2)
- Flat top cover (24RU racks only)
- Gland plates fitted to roof (40 & 45RU racks only)
- Bolt down brackets

Model Sizes

600mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AS24U609	24	1202	600	900
AS24U611	24	1202	600	1100
AS40U609	40	1913	600	900
AS40U611	40	1913	600	1100
AS45U609	45	2135	600	900
AS45U611	45	2135	600	1100

For dimension drawing see page 56

800mm Wide

Model No	Height (RU)	Dimensions (mm)		
		Height	Width	Depth
AS40U809	40	1913	800	900
AS40U811	40	1913	800	1100
AS45U809	45	2135	800	900
AS45U811	45	2135	800	1100

For dimension drawing see page 57



Accessories Guide

Accessories	Page
Cable zone	14
Cable management	15
Power rails	16
Shelves	17
Cable trays	18
Blanking panels	18
Fan kit	19
General accessories	19